


TERRAJAS PARA ROSCAR A MANO

BSF

- **Ejecución:** HSS, DIN 223.
- Diámetro previo de la varilla para el roscado.




151166

Unid:mm

HSS

DIN
223



CÓDIGO	ROSCA-HILOS	D	L	Ø
1032	BSF 3/16-32h	20	7	4,67
1426	BSF 1/4-26h	20	7	6,25
1622	BSF 5/16-22h	25	9	7,82
1820	BSF 3/8-20h	30	11	9,39
2018	BSF 7/16-18h	30	11	10,97
2216	BSF 1/2-16h	38	10	12,54
2416	BSF 9/16-16h	38	10	14,12
2614	BSF 5/8-14h	45	14	15,71
3012	BSF 3/4-12h	45	14	18,85
3211	BSF 7/8-11h	55	22	22,02
3410	BSF 1-10h	55	22	25,17

Aceros Carbono	Aceros Aleados	Aceros Preendurecidos	Aceros Endurecidos		Fundición	Aluminio	Inoxidable	Titanio	Cobre	Bronce	CFRP
~HB225 ⊙	HB225 ~325	HRc30~45	HRc 45 ~55	HRc 55~							

- Consulten plazo de entrega.

⊙ : Excelente

○ : Bueno